



## Item # 20448190, ARVAC SW Abrasive / Corrosive Hose 4 in x 100 ft, 30 psi, Black

**APPLICATION:** Heavy-duty abrasion-resistant suction hose used for a variety of abrasive material-handling applications, including the transfer of sand, gravel, cement, fly ash, glass, metals, plastic pellets, fertilizers, rock salts and slurries. Static wire for static dissipation.

**CONSTRUCTION TUBE:** Higher-temperature urethane

**COVER:** Static-dissipating thermoplastic alloyed blend of nitrile, polyurethane and PVC

**REINFORCEMENT:** Rigid high-density PVC helix

**TEMPERATURE:** -40 °F to 158 °F (-40 °C to 70 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Not branded



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Abrasive Transfer
Style	Abrasive / Corrosive Hose
Construction Tube	Higher-temperature urethane
Cover	Static-dissipating thermoplastic alloyed blend of nitrile, polyurethane and PVC

<b>Reinforcement</b>	Rigid high-density PVC helix
<b>Color</b>	Black
<b>Min. Temperature</b>	-40 °F -40 °C
<b>Max. Temperature</b>	158 °F 70 °C
<b>Max. Working Pressure</b>	30.0 psi 0.21 MPa
<b>Brand</b>	ARVAC™ SW
<b>Order Code</b>	586-550

### Specifications

<b>I.D.</b>	4 in 101.60 mm
<b>Nom. O.D.</b>	4.740 in 120.50 mm
<b>Total Width</b>	4.740 in 120.50 mm
<b>Length</b>	100.000 ft
<b>Bend Radius</b>	7.000 in 177.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	1.970 lb/ft 2.91 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)  
 1-800-235-4632  
 Contitech.us

**ContiTech**