

## Forestry Grade Ball Shut-Off Nozzles

**Features:**

- NFPA1964 compliant
- hardcoated threads, and acetal ball, rigid inlet
- maximum operating pressure: **600 PSI** at ambient temperature (70°F)
- FSS specification 5100-238

Size	Thread	Waterway	Anodized Aluminum Part #	Price/E
1"	NPSH	¾"	<b>FBSO100S</b>	<b>\$384.00</b>
1½"	NPSH	1"	<b>FBSO150S</b>	<b>394.10</b>
1"	NST (NH)	¾"	<b>FBSO100F</b>	<b>398.95</b>
1½"	NST (NH)	1"	<b>FBSO150F</b>	<b>350.00</b>



## Forestry Grade Ball Shut-Off Nozzle with Pistol Grip

**Features:**

- NFPA1964 compliant
- hardcoated threads, and acetal ball, full time live swivel inlet
- maximum operating pressure: **600 PSI** at ambient temperature (70°F)
- FSS specification 5100-238

Size	Thread	Waterway	Anodized Aluminum Part #	Price/E
1"	NPSH	¾"	<b>FBSO100S-PG</b>	<b>\$564.25</b>
1½"	NPSH	1"	<b>FBSO150S-PG</b>	<b>596.50</b>
1"	NST (NH)	¾"	<b>FBSO100F-PG</b>	<b>520.70</b>
1½"	NST (NH)	1"	<b>FBSO150F-PG</b>	<b>596.50</b>



## Break Apart Attack Nozzles

**Application:**

- low-cost, versatile, and easy-to-use nozzle for first responders in rural and suburban fire departments

**Features:**

- minimal training is required to connect and operate the nozzle
- nozzle uses a 1½" coupler, provides 20-90 GPM fog or straight stream flows at **100 PSI**
- nozzle can be separated from the shut off valve for extended hose lays and other uses
- this product meets or exceeds USDA Forestry Service standards

Size	Thread	Aluminum Part #	Price/E
1"	NPSH	<b>ABN100S</b>	<b>\$807.85</b>
1"	NST (NH)	<b>ABN100F</b>	<b>807.85</b>
1½"	NPSH	<b>ABN150S</b>	<b>897.85</b>
1½"	NST (NH)	<b>ABN150F</b>	<b>897.85</b>



P

## Tip for Ball Shut-Off Nozzles

**Features:**

- lightweight
- maximum operating pressure: **200 PSI** (water only) at ambient temperature (70°F)

Size	Thread	Orifice <sup>1</sup>	Length	Anodized Aluminum Part #	Price/E
1"	NPSH	½"	4"	<b>ANT100</b>	<b>\$261.60</b>
1½"	NPSH	½"	4¾"	<b>ANT150</b>	<b>238.55</b>
1"	NST (NH)	½"	4"	<b>ANT100F</b>	<b>271.80</b>
1½"	NST (NH)	½"	4¾"	<b>ANT150F</b>	<b>238.55</b>



<sup>1</sup> other orifice sizes available, contact Dixon™