

Constant Flow Nozzles

Features:

- shatterproof and UV resistant polycarbonate withstands tough environmental conditions
- seals used for true water shut off
- easy twist spray pattern adjustment
- sold in case quantity only, with display
- 25 nozzles per case



Thread	45° Spray GPM @ 100 PSI	Color	Global Part #	Price/E
3/4" GHT	25.1	green	FNB75GHT-GD	\$493.00
3/4" GHT	25.1	clear	CNB75GHT-GD	493.00

NEW

Constant Flow Nozzles with Bumper

Feature:

- can be used as a replacement nozzle in the display case GNB75GHT-GD



Thread	45° Spray GPM @ 100 PSI	Color	Plastic Part #	Price/E
3/4" GHT	8	green	GNB75GHT (domestic)	\$26.20
3/4" GHT	25.1	clear	CNB75GHT (global)	21.20

NEW

Red Plain Hose Nozzles

Feature:

- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)



Size	Thread	Length	Orifice	Red Polycarbonate Part #	Price/E
1 1/2"	NPSH	10"	1/2"	PN15	\$18.00
1 1/2"	NPSH	10"	1/2"	PN15CF	18.00
1 1/2"	NST (NH)	10"	1/2"	PN15F	18.00
1 1/2"	NST (NH)	10"	1/2"	PN15NYFD	18.00

Penetrator Nozzles

Features:

- designed with standard 1 1/2" NPSH male hose threads that are converted to female thread for connection to the hose using a double female rigid connector
- 1/4" discharge orifice generates a high velocity water jet that is effective against deep seated wildland fires
- maximum operating pressure: **200 PSI** (water only) at ambient temperature (70°F)



Size	Thread	Length	Orifice	Polycarbonate Part #	Price/E
1 1/2"	NPSH	5 1/2"	1/4"	PFN4005S	\$51.55
1 1/2"	NST (NH)	5 1/2"	1/4"	PFN4005F	51.55

Twin Tip Straight Stream Forestry Nozzles

Features:

- molded high strength red polycarbonate
- solid, one-piece reversible twin tip has 1/4" and 3/8" orifices
- maximum operating pressure: **100 PSI** (water only) at ambient temperature (70°F)



Size	Thread	Length with tip	Length without tip	Orifice of base nozzle	Polycarbonate Part #	Price/E
1 1/2"	NPSH	9"	7 1/2"	1/2"	PTTF150S	\$32.10
1 1/2"	NST (NH)	9"	7 1/2"	1/2"	PTTF150F	32.10