



The Right Connection®

Diesel Exhaust Fluid (DEF) Automatic Shutoff Nozzle and Fittings

Application:

- designed to transfer diesel exhaust fluid

Features:

- body is double coated inside and out with baked on PTFE
- maximum operating pressure: **50 PSI**

Materials:

- body: aluminum
- spout: stainless steel
- wetted parts: stainless, acetal, PTFE
- seals: FKM-A

Size:

- 3/4"



NPT Inlet	Spout Outlet	Weight (lbs)	Approximate Flow Rate at 20 PSI (GPM)	Part #
3/4"	13/16"	2 1/2	14	DEFN075

External Swage/Crimp Uni-Range Male Couplings

Applications:

- for use on most one or two wire braid reinforced hoses, fiber reinforced with or without helical wire

Features:


- designed for 1/2" - 1" hose systems
- can be swaged, crimped or clamped

Materials:

- stem: 316 stainless steel
- ferrule: 304 stainless steel

Sizes:

- 1/2", 3/4" and 1"



For Crimping



For Use With Clamps*

Hose ID	Thread	Hose OD		Stainless Steel Part #*
		From	To	
1/2"	NPT	58/64"	62/64"	R8P2SS
	NPT	1-6/64	1-12/64	R12P1250
3/4"	BSPT	1-6/64"	1-12/64	R12P1250A
	NPT	1-13/64"	1-22/64	R12P1370
	NPT	1-30/64"	1-38/64"	R16P1620
1"	NPT	1-38/64"	1-46/64"	R16P1770

Hose ID	Thread	316 Stainless Steel Part #*
1/2"	NPT	MR0808
	NPT	MR1212
3/4"	BSPT	MR1212A
	NPT	MR1616

* Should be used with stainless steel preformed band clamps

*Please contact Dixon for crimp specifications

Supplementary Fittings and Accessories for Diesel Exhaust Fluid Applications

Fittings

Dixon offers stainless steel and polypropylene:

- cam & groove
- king combination nipples
- male inserts



Dry Disconnects and Break Aways


Dixon offers stainless steel:

- dry disconnect couplers and dust plugs
- dry disconnect adapters and dust caps
- industrial safety break-away couplings
- marine safety break-away couplings

Accessories

Dixon offers stainless steel:

- valves
- gauges



Dixon

800 High Street • Chestertown, MD 21620 • ph 877.963.4966 • fx 800.283.4966

dixonvalve.com

Printed in the USA