


SPX

INDEXABLE END MILL FOR
DEEP SHOULDER MILLING



TOOL NEWS B111A

Indexable End Mill for Deep Shoulder Milling

SPX

Features

Insert

Wavy cutting edge type

WH Breaker		
Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge

The wavy cutting edge gradually engages the workpiece.

Reduced impact when entering the workpiece.

Chip cross section

Uses the same cutting edge theory as a solid type roughing end mill.


Lower cutting resistance

Straight cutting edge type

JM Breaker		
Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge

High clamping rigidity

The high clamping and positional rigidity of the inserts prevents damage to the cutting edge even under the harshest conditions.




Spiral relief cut

Prevents chip packing and damage to the tool body without hindering the overall tool rigidity.




Cutting performance


Low Cutting Resistance



Chip Breaking



<Cutting conditions>
Workpiece : Ductile cast iron
Cutting speed : 330 SFM
Feed per tooth : .008 IPT
Depth of cut : 1.969 inch
Width of cut : .197 inch
Dry cutting




SPX


Shank Type



CAT50 shank



Straight shank (Combination type)



Light Alloy	Cast Iron	Carbon Steel Alloy Steel	Stainless Steel	Hardened Steel

Right hand tool holder only.

Type	Order Number	Stock	Number of Flute	Number of Teeth		Dimensions (inch)					Number of Insert		
				Total	Bottom	D1	L1	D4	L2	ap	Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge
											JPMX 190412- 	MPMX 120412- 	SPMX 120408- 
CAT50 Shank	SPX4R3224CAT50NS	●	2	24	4	2.000	11.000	—	7.000	4.300	2	2	20
	4R3234CAT50NM	●	2	34	4	2.000	13.000	—	9.000	6.200	2	2	30
	4R3244CAT50NL	●	2	44	4	2.000	15.000	—	11.000	8.100	2	2	40
Straight Shank (Combination)	SPX4R05016WNES	●	2	16	4	1.969	7.091	2.000	3.937	2.835	2	2	12
	4R05024WNS	●	2	24	4	1.969	8.661	2.000	5.512	4.331	2	2	20
	4R05034WNM	●	2	34	4	1.969	10.630	2.000	7.480	6.181	2	2	30
	4R05044WNL	●	2	44	4	1.969	12.598	2.000	9.449	8.071	2	2	40

Spare Parts

Holder				Insert		
	Clamp Screw	Wrench	Anti-seizure Lubricant	Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge
SPX	TS55	TKY25D	MK1KS	JPMX190412-WH	MPMX120412-WH	SPMX120408-WH
				JPMX190412-JM	MPMX120412-JM	SPMX120408-JM

* Clamp Torque (lbf-in) : TS55=66



● : USA Stock (10 inserts in one case)

Indexable End Mill for Deep Shoulder Milling

SPX

Shell Type

NEW



Right hand tool holder only.

Light Alloy	Cast Iron	Carbon Steel Alloy Steel	Stainless Steel	Hardened Steel



D1	Clamping Bolt Order Number	Geometry
φ2.500"	HSCUF50028	
φ3.000"	62528	

Order Number	Stock	Number of Teeth			Dimensions (inch)								Number of Insert		
													Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge
	R	Flutes	Total	Bottom	D1	L1	D9	L7	D8	W1	L8	ap	JPMX 140412-○○	MPMX 120412-○○	SPMX 120408-○○
SPX4UR2524CA22A	●	4	24	4	2.500	3.500	1.000	1.339	.539	.375	.219	2.280	2	2	20
4UR0324DA22A	●	4	24	4	3.000	3.500	1.250	1.654	.669	.500	.281	2.280	2	2	20

(Note) In case of internal coolant supply, please use a face mill arbor with through coolant channels. Regular center-thru or side-thru arbors can't be used.

Shell Type

NEW



Right hand tool holder only.

METRIC Standard
For inch arbors



D1	Clamping Bolt Order Number	Geometry
φ63mm	HSC12070	
φ80mm	16065	

Order Number	Stock	Number of Teeth		Dimensions (mm)									Number of Insert		
													Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge
	R	Flutes	Total	Bottom	D1	L1	D9	L7	D8	W1	L8	ap	JPMX 140412-○○	MPMX 120412-○○	SPMX 120408-○○
SPX4R06324CA058A	★	4	24	4	63	85	25.4(1.000")	26	13	9.5	6	58	2	2	20
4R08024DA058A	★	4	24	4	80	85	31.75(1.250")	38	17	12.7	8	58	2	2	20

(Note) In case of internal coolant supply, please use a face mill arbor with through coolant channels. Regular center-thru or side-thru arbors can't be used.

Shell Type

NEW



Right hand tool holder only.

METRIC Standard
For metric arbors
The bore diameter (D9) is equivalent to a metric size.

D1	Clamping Bolt Order Number	Geometry
φ63mm	HSC12070	
φ80mm	16065	

Order Number	Stock	Number of Teeth		Dimensions (mm)									Number of Insert		
													Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge
	R	Flutes	Total	Bottom	D1	L1	D9	L7	D8	W1	L8	ap	JPMX 140412-○○	MPMX 120412-○○	SPMX 120408-○○
SPX4-063A24A058RA	★	4	24	4	63	85	27	28	13	12.4	7	58	2	2	20
-080A24A058RA	★	4	24	4	80	85	32	40	17	14.4	8	58	2	2	20

(Note) In case of internal coolant supply, please use a face mill arbor with through coolant channels. Regular center-thru or side-thru arbors can't be used.

● : USA Stock ★ : Inventory maintained in Japan.

Spare Parts

Holder						
	Clamp Screw	Wrench	Anti-seizure Lubricant	Bottom Cutting Edge A	Bottom Cutting Edge B	Peripheral Cutting Edge
SPX	TS55	TKY25D	MK1KS	JPMX140412-WH	MPMX120412-WH	SPMX120408-WH
				JPMX140412-JM	MPMX120412-JM	SPMX120408-JM


★ Clamp Torque (N • m) : TS55=7.5.

Inserts

Type	Shape	Order Number	Class	Coated			Dimensions (mm)					Geometry
				VP15TF	VP20RT		L1	L2	D1	S1	Re	
Wavy Cutting Edge Type (WH Breaker)	Bottom Cutting Edge A	JPMX190412-WH * 140412-WH	M	●	●		.750	.500	—	.187	.047	
	Bottom Cutting Edge B	MPMX120412-WH	M	●	●		—	—	.500	.187	.047	
	Peripheral Cutting Edge	SPMX120408-WH	M	●	●		—	—	.500	.187	.031	
Straight Cutting Edge Type (JM Breaker)	Bottom Cutting Edge A	JPMX190412-JM * 140412-JM	M	●	●		.750	.500	—	.187	.047	
	Bottom Cutting Edge B	MPMX120412-JM	M	●	●		—	—	.500	.187	.047	
	Peripheral Cutting Edge	SPMX120408-JM	M	●	●		—	—	.500	.187	.031	

★ Only for use with a shell type holder.

Indexable End Mill for Deep Shoulder Milling



Recommended Cutting Conditions (Shank Type)

Cutting Conditions for Shoulder Milling (Number of effective flutes is 2.)

	Work Material	Hardness	Insert Grade/Breaker	Cutting Speed vc (SFM)	Width of Cut ae (inch)	Depth of Cut ap (inch)	Feed per Tooth fz (IPT)
P	Mild Steel	≤180HB	VP15TF WH	395 (330—460)	<.394	<4D1	.006— .010
			VP15TF JM	395 (330—460)	<.394	<2D1	.006— .010
	Carbon Steel Alloy Steel	180—350HB	VP15TF WH	260 (230—395)	<.394	<4D1	.006— .010
			VP15TF JM	260 (230—395)	<.394	<2D1	.006— .010
	Alloy Tool Steel	≤300HB	VP15TF WH	260 (200—330)	<.394	<4D1	.004— .008
			VP15TF JM	260 (200—330)	<.394	<2D1	.004— .008
M	Stainless Steel	≤200HB	VP20RT WH	260 (230—395)	<.394	<4D1	.004— .008
			VP20RT JM	260 (230—395)	<.394	<2D1	.004— .008
K	Cast Iron	Tensile Strength ≤350MPa	VP15TF WH	330 (260—395)	<.394	<4D1	.006— .016
			VP15TF JM	330 (260—395)	<.394	<4D1	.004— .010
	Ductile Cast Iron	Tensile Strength ≤800MPa	VP15TF WH	260 (200—330)	<.394	<4D1	.006— .014
			VP15TF JM	260 (200—330)	<.394	<4D1	.004— .008
S	Titanium Alloy	≤350HB	VP20RT WH	130 (115—165)	<.394	<4D1	.003— .005
			VP20RT JM	130 (115—165)	<.394	<2D1	.003— .005

(Note 1) The above cutting conditons are determined based on high rigidity machine and workpiece, where no vibration occurred.
Please adjust processing conditions if the vibration is generated.

(Note 2) For tools with a cutting edge length of 7.87" or more, please reduce the cutting speed and table feed by 10-20% and the width of cut by 50%.

(Note 3) If the cutting angle between the tool and workpiece exceeds 90° when machining corners ,Reduce the cutting speed and table feed by 10-20% and ae by 50%. Also if possible, set a radius cutting path for corners.

Cutting Conditions for Slot Milling

	Work Material	Hardness	Insert Grade/Breaker	Cutting Speed vc (SFM)	Width of Cut ae (inch)	Depth of Cut ap (inch)	Feed per Tooth fz (IPT)
P	Mild Steel	≤180HB	VP15TF WH	200 (165—395)	D1	<.394	.004— .010
			VP15TF JM	200 (165—395)	D1	<.394	.004— .006
	Carbon Steel Alloy Steel	180—350HB	VP15TF WH	200 (165—330)	D1	<.394	.004— .010
			VP15TF JM	200 (165—330)	D1	<.394	.004— .006
	Alloy Tool Steel	≤300HB	VP15TF WH	165 (130—260)	D1	<.394	.004— .010
			VP15TF JM	165 (130—260)	D1	<.394	.004— .006
M	Stainless Steel	≤200HB	VP20RT WH	200 (165—395)	D1	<.394	.004— .010
			VP20RT JM	200 (165—395)	D1	<.394	.004— .006
K	Cast Iron	Tensile Strength ≤350MPa	VP15TF WH	165 (130—260)	D1	<1.969	.006— .010
			VP15TF JM	165 (130—260)	D1	<1.575	.004— .008
	Ductile Cast Iron	Tensile Strength ≤800MPa	VP15TF WH	130 (115—260)	D1	<1.575	.006— .010
			VP15TF JM	130 (115—260)	D1	<1.181	.004— .008
S	Titanium Alloy	≤350HB	VP20RT WH	115 (100—165)	D1	<.394	.003— .005
			VP20RT JM	115 (100—165)	D1	<.394	.003— .005

(Note 1) The above cutting conditons are determined based on high rigidity machine and workpiece, where no vibration occurred.
Please adjust processing conditions if the vibration is generated.



Recommended Cutting Conditions (Shell Type)

Cutting Conditions for Shoulder Milling (Number of effective flutes is 4.)

	Work Material	Hardness	Insert Grade/Breaker	Cutting Speed vc (SFM)	Width of Cut ae (inch)	Depth of Cut ap (inch)	Feed per Tooth fz (IPT)
P	Mild Steel	≤180HB	VP15TF JM	395 (330—460)	<.394	<0.5D1	.006— .012
				395 (330—460)	<.394	>0.5D1	.006— .010
	Carbon Steel Alloy Steel	180—350HB	VP15TF JM	395 (260—425)	<.394	<0.5D1	.006— .012
				330 (260—395)	<.394	>0.5D1	.006— .010
	Alloy Tool Steel	≤300HB	VP15TF JM	330 (200—360)	<.394	<0.5D1	.004— .010
				260 (200—330)	<.394	>0.5D1	.004— .006
M	Stainless Steel	≤200HB	VP20RT JM	460 (330—490)	<.394	<0.5D1	.004— .010
				395 (330—460)	<.394	>0.5D1	.004— .008
K	Cast Iron	Tensile Strength ≤350MPa	VP15TF WH	395 (260—425)	<.394	<0.5D1	.010— .016
				330 (260—395)	<.394	>0.5D1	.010— .016
			VP15TF JM	395 (260—425)	<.394	<0.5D1	.006— .012
				330 (260—395)	<.394	>0.5D1	.006— .010
	Ductile Cast Iron	Tensile Strength ≤800MPa	VP15TF WH	330 (200—360)	<.394	<0.5D1	.008— .014
				260 (200—360)	<.394	>0.5D1	.008— .014
S	Titanium Alloy	≤350HB	VP15TF JM	330 (200—395)	<.394	<0.5D1	.006— .012
				260 (200—395)	<.394	>0.5D1	.006— .012
			VP20RT JM	150 (115—165)	<.394	<0.5D1	.003— .004
				150 (115—165)	<.394	>0.5D1	.003— .004

(Note 1) The above cutting conditons are determined based on high rigidity machine and workpiece, where no vibration occurred.
Please adjust processing conditions if the vibration is generated.




Cutting Conditions for Slot Milling

	Work Material	Hardness	Insert Grade/Breaker	Cutting Speed vc (SFM)	Width of Cut ae (inch)	Depth of Cut ap (inch)	Feed per Tooth fz (IPT)
P	Mild Steel	≤180HB	VP15TF JM	395 (330—460)	D1	<0.25D1	.006— .010
	Carbon Steel Alloy Steel	180—350HB	VP15TF JM	330 (260—395)	D1	<0.25D1	.006— .010
	Alloy Tool Steel	≤300HB	VP15TF JM	260 (200—330)	D1	<.394	.004— .008
M	Stainless Steel	≤200HB	VP20RT JM	330 (260—460)	D1	<.394	.004— .006
K	Cast Iron	Tensile Strength ≤350MPa	VP15TF WH	260 (200—330)	D1	<0.25D1	.004— .010
				200 (165—330)	D1	<0.6D1	.004— .008
			VP15TF JM	260 (200—330)	D1	<0.25D1	.004— .008
				200 (165—330)	D1	<0.6D1	.004— .006
	Ductile Cast Iron	Tensile Strength ≤800MPa	VP15TF WH	260 (200—330)	D1	<0.25D1	.004— .010
				200 (165—330)	D1	<0.5D1	.004— .008
S	Titanium Alloy	≤350HB	VP15TF JM	260 (200—330)	D1	<0.25D1	.004— .008
				200 (165—330)	D1	<0.5D1	.004— .006
S	Titanium Alloy	≤350HB	VP20RT JM	130 (115—165)	D1	<0.25D1	.002— .004
				130 (115—165)	D1	<0.25D1	.002— .004

(Note 1) The above cutting conditons are determined based on high rigidity machine and workpiece, where no vibration occurred.
Please adjust processing conditions if the vibration is generated.

SPX

Tool		SPX4R05034WNM	SPX4R05034WNM	SPX4UR2524CA22A
Grade / Breaker		VP15TF / WH breaker	VP20RT / WH breaker	VP15TF / WH breaker
Workpiece		Cast iron	Ductile cast iron	Cast iron
Component		Press molds (Base)	Press molds (Trim)	Press molds
Cutting Conditions	Cutting Speed (SFM)	330	330	410
	Table Feed (IPM)	20.04	17.52	29.84
	Feed per Tooth (IPT)	.016	.014	.012
	Depth of Cut (inch)	4.921	1.969—3.937	2.165
	Width of Cut (inch)	.315—.394	.197—.315	.394—.591
Coolant		Dry	Dry	Dry
Results		In comparison with the conventional product overall machining efficiency was doubled. Stable tool life due to effective chip control and low cutting resistance was also achieved.	In comparison with the conventional product overall machining efficiency was increased by 70%.	In comparison to conventional product, SPX provided low cutting resistance and 3x higher productivity. This allowed for a reduction in processing time.

Tool		SPX4UR2524CA22A	SPX4UR2524CA22A	SPX4UR2524CA22A
Grade / Breaker		VP15TF / WH breaker	VP20RT / JM breaker	VP20RT / JM breaker
Workpiece		Ductile cast iron 	Titanium alloy 	Stainless steel 
Component		Machine parts	Aerospace parts	Machine parts
Cutting Conditions	Cutting Speed (SFM)	395	150	395
	Table Feed (IPM)	19.09	3.58	9.52
	Feed per Tooth (IPT)	.008	.004	.004
	Depth of Cut (inch)	1.969	1.772	1.772
	Width of Cut (inch)	.197—.591	.394—.984	.394
Coolant		Dry	Wet	Wet
Results		In comparison to conventional product, SPX provided low cutting resistance and 3x higher productivity. This allowed for a reduction in processing time.	In comparison to a conventional product, SPX provided 1.5x better tool life. This allowed for a reduction in tool cost.	In comparison to conventional product, SPX provided low cutting resistance and 4.8x higher productivity. This allowed for a reduction in processing time.



MACHINING TECHNOLOGY
AND EDUCATION CENTER

Welcome to our new world-class
Machining Technology and Education
Center (MTEC) in Mooresville, NC
providing year round support and
services to North America.



ABOUT MTEC

TOOLING PROPOSALS & EVALUATION

We will review your current processes or outline a new process. From this review, we will improve productivity, analyze programming methods and output a solution with programming, tooling and time savings.

MACHINING SIMULATION

Using the latest CAD/CAM software and our cutting tool experience, we will outline a new process using proper machining techniques to maximize tool life and productivity.

TECHNICAL SUPPORT

Dedicated local professionals to answer any of your order, product or technical questions.

TRAINING

We are excited to offer several levels of training with goals to reach our highest level--Craftsman Machining Technology. At MTEC NC, we will train using a combination of classroom and hands-on machine time to develop skills and real-world understanding of materials, tools and applications. In addition to multi-day courses, we will have Machining Technology skills seminars, as well as seminars from our partners to complement our apprentice level courses, our journeyman courses, and up to our craftsman level courses.

PROCESS IMPROVEMENTS

Review of the complete part processing and recommend changes of speed, feed, new tooling, reduction of passes, modifying programming and other solutions to reduce cycle time, save money and be proactive.



WEBINARS

Our FREE online webinar series is available anytime on-demand. Narrated by the MTEC training staff, you will receive in-depth knowledge of the topic. Simply register online at the link below for access. You will receive a certificate upon completion of each course.

mmusnewsstand.com/register

ONLINE TRAINING

Our FREE e-learning program offers 11 courses in drilling, milling, turning, threading, tool grades and workpiece materials. Once each course is completed, you will be given the opportunity to print a certificate.

- Basic Drilling
- Basic Milling
- Basic Turning
- Advanced Drilling
- Advanced End Milling
- Advanced Turning
- Basic Threading
- Advanced Face Milling
- Basic Workpiece Materials
- Tool Grades
- Advanced Workpiece Materials

TRAINING COURSES

Programs are designed for several levels of skill development – from basic understanding to advance manufacturing with digital solutions, complementing to your valued experience in CNC machining environment. Participate in machining demonstrations with Mitsubishi Materials' skilled engineers. Discover methods to reduce setup and cycle time, optimize programs and enhance your knowledge base.

Information on course schedule,
course description, and accommodations

MTECTRaining.INFO

Follow the QR Code for a virtual facility tour





MITSUBISHI MATERIALS U.S.A. CORPORATION

California Office (Headquarters)

3535 Hyland Avenue, Suite 200
Costa Mesa, CA 92626
Customer Service: 800.523.0800
Technical Service: 800.486.2341

Chicago Office (Engineering)

300 N. Martingale Road, Suite 500
Schaumburg, IL 60173
Main: 847.252.6300
Fax: 847.519.1732

MMC Metal de Mexico, S.A. DE C.V.

Av. La Cañada No.16,
Parque Industrial Bernardo
Quintana, El Marques,
Queretaro C.P. 76246 MEXICO
Main: +52.442.221.61.36
Fax: +52.442.221.61.34

North Carolina-MTEC (Marketing & Technical Center)

105 Corporate Center Drive, Suite A
Mooresville, NC 28117
Main: 980.312.3100
Fax: 704.746.9292

Toronto Office (Canada Branch)

600 Matheson Blvd. Unit 5 (Office)
Mississauga, ON L5R 4C1
Main: 905.814.0240
Fax: 905.814.0245

Detroit Office (Moldino CS)

41700 Gardenbrook Road, Suite 120
Novi, MI 48375
Main: 248.308.2620
Fax: 248.308.2627

FOR YOUR SAFETY

- Don't handle inserts and chips without gloves.
- Please machine within the recommended application range and exchange expired tools with new ones in advance of breakage.
- Please use safety covers and wear safety glasses.
- When using compounded cutting oils, please take fire precautions.
- When attaching inserts or spare parts, please use only the correct wrench or driver.
- When using rotating tools, please make a trial run to check run-out, vibration and abnormal sounds etc.

www.mmc-carbide.com/us

Tools specifications subject to change without notice.

B111A-US-2010.7