



Item # 20017496, FLEXWING Petroleum Transfer Hose 2 in x 100 ft, 150 psi, Black

APPLICATION: For use in tank truck and in-plant operations to transfer gasoline, oil, ethanol blends and other petroleum base products up to 50% aromatic content. It is designed for pressure, gravity flow, or full-suction service.

CONSTRUCTION TUBE: Nitrile synthetic rubber RMA Class A (High Oil Resistance)

COVER: Black (red spiral stripe) or Red Chemivic™ (white spiral stripe) synthetic rubber (oil resistant); smooth cover; wrapped finish

REINFORCEMENT: Spiral-plyed synthetic fabric with wire helix

TEMPERATURE: -35 °F to 200 °F (-37 °C to 93 °C)

COUPLINGS: Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING (SPIRAL): Example: Continental Contitech Flexwing® Petroleum 150 psi WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petroleum Transfer
Style	Petrol Transfer Hose
Construction Tube	Nitrile synthetic rubber RMA Class A (High Oil Resistance)
Cover	Black (red spiral stripe) Chemivic™ synthetic rubber (oil resistant); smooth cover; wrapped finish
Reinforcement	Spiral-plyed synthetic fabric with wire helix

Color	Black
Min. Temperature	-35 °F -37 °C
Max. Temperature	200 °F 93 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	PLICORD® FLEXWING®
Order Code	543-109

Specifications

I.D.	2 in 50.80 mm
Nom. O.D.	2.550 in 64.80 mm
Length	100.000 ft
Bend Radius	5.000 in 114.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.300 lb/ft 1.93 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech