



Item # 20019277, BLACK SOFTWALL Bulk Transfer Hose (1/4" Tube Gauge) 6 in x 100 ft, 50 PSI, Black

APPLICATION: For the discharge of dry bulk cement from tank truck and in-plant service.

CONSTRUCTION TUBE: 1/8" (static dissipating/static conductive) Black CHEMITUF(compound)® synthetic rubber. Available in 1/8", 3/16", and 1/4" tube gauges.

COVER: Black SBR(compound)® synthetic rubber with white spiral stripe (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric

TEMPERATURE: -25 °F to 180 °F (-32 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING (SPIRAL): Example: Continental Contitech Black Softwall.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Dry Bulk Cement Transfer
Style	Bulk Transfer Hose
Construction Tube	1/8" (static dissipating/static conductive) Black Tufsyn® synthetic rubber. Available in 1/8", 3/16", and 1/4" tube gauges.
Cover	Black Plioflex® synthetic rubber with white spiral stripe (wrapped impression)

Reinforcement	Spiral-plyed synthetic fabric
Color	Black
Min. Temperature	-25 °F -32 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	50.0 psi 0.34 MPa
Brand	BLACK SOFTWALL
Order Code	549-148

Specifications

I.D.	6 in 152.40 mm
Nom. O.D.	6.450 in 163.83 mm
Total Width	6.450 in 163.83 mm
Length	100.000 ft
Weight	2.250 lb/ft 3.35 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech