



Item # 20019671, PYROFLEX HOT AIR Material Handling Hose 3 in x 100 ft, 50 psi, Black

APPLICATION: For conveying hot air from compressors to tanks on bulk dry material carriers.

CONSTRUCTION TUBE: Black heat-resistant EPDM(compound)[®] synthetic rubber

COVER: Heat-resistant black EPDM(compound) synthetic rubber with orange spiral stripe (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric with wire helix

TEMPERATURE: -20 °F to 325 °F (-29 °C to 163 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product. See the Couplings Systems information pages at the back of the catalog.

BRANDING (SPIRAL): Example: Continental Contitech Pyroflex[®] II Hot Air.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Air and Multipurpose Transfer
Style	Air and Multipurpose Hose
Reinforcement	Spiral-plied synthetic fabric with wire helix
Cover	Heat-resistant black Versigard synthetic rubber with orange spiral stripe (wrapped impression)
Construction Tube	Black heat-resistant Versigard [®] synthetic rubber

Color	Black
Min. Temperature	-20 °F -29 °C
Max. Temperature	325 °F 163 °C
Max. Working Pressure	50.0 psi 0.34 MPa
Packaging	Coil
Brand	PYROFLEX® II HOT AIR
Order Code	549-394
Edited By: Initials and Date	SAS 11/27/12

Specifications

I.D.	3 in 76.20 mm
Nom. O.D.	3.550 in 90.20 mm
Bend Radius	7.000 in 178.00 mm
Length	100.000 ft
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.930 lb/ft 2.87 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech