



## Item # 20146766, ARCTIC ORTAC PLUS Air & Multipurpose Hose 1 in x 500 ft, 300 psi, Black

**APPLICATION:** A low-temperature hose construction for air, water, oil, kerosene, fuel oil and some chemical operations where temperatures fall as low as -65 °F (-54 °C).

**CONSTRUCTION TUBE:** Black low-temp, ECO oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

**COVER:** Black ultra-low temperature, ECO oil resistant synthetic rubber (with a blue stripe), RMA Class A (High Oil Resistance)

**REINFORCEMENT:** One textile braid

**TEMPERATURE:** -65 °F to 180 °F (-54 °C to 82 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: 9.5 mm 3/8" Arctic Ortac® Plus 2.1 MPA/300 psi Continental Contitech Made in the U.S.A.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Air and Multipurpose Transfer
Style	Air and Multipurpose Hose
Reinforcement	One textile braid
Cover	Black ultra-low temperature, ECO oil resistant synthetic rubber (with a blue stripe), RMA Class A (High Oil Resistance)
Construction Tube	Black low-temp, ECO oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

<b>Color</b>	Black
<b>Min. Temperature</b>	-65 °F -54 °C
<b>Max. Temperature</b>	180 °F 82 °C
<b>Max. Working Pressure</b>	300.0 psi 2.07 MPa
<b>Packaging</b>	Reel
<b>Brand</b>	ARCTIC ORTAC®
<b>Order Code</b>	536-275

### Specifications

<b>I.D.</b>	1 in 25.40 mm
<b>Nom. O.D.</b>	1.500 in 38.10 mm
<b>Length</b>	500.000 ft
<b>Weight</b>	0.570 lb/ft 0.86 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)  
 1-800-235-4632  
 Contitech.us

**ContiTech**