



3/8" DRIVE TOOLS

Receive Extra 20% Off of Standard Discount

RATCHET WRENCHES

- Steel Angle Head
- Aluminum Housing
- Ergonomic Composite Grip

Model Number	Drive Size		Bolt Cap Grade 5		Maximum Torque		Free Speed		Weight		Length		Avg Air Consumption	
	in	mm	in	mm	ft lb	Nm	rpm	lb	kg	in	mm	cfm	l/s	
5007	3/8	9.5	5/16	8	20	27	265	1.3	0.55	6.6	168	1.4	0.7	
5011	3/8	9.5	7/16	11	50	68	185	2.6	1.2	10.8	274	3.0	1.4	

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm)
 Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Head Cover • Parts List • Safety and Instruction Manual

- Lever Start
- Teasing Throttle
- Comfort Grip

Model Number	Drive Size		Torque		Free Speed		Weight		Length		Side to Center		Air Consumption		Exhaust
	in	mm	ft lb	Nm	rpm	lb	kg	in	mm	in	mm	cfm	l/s		
0.3 hp (0.25 kW)															
SRW03S-25	1/4"	9.5	35	47	235	1.4	0.6	7.7	197	1.1	28	11	5.2	Rear	
SRW03S-38	3/8"	9.5	35	47	235	1.4	0.6	7.7	197	1.1	28	11	5.2	Rear	
SRW03S-38Q	3/8"	9.5	35	47	235	1.4	0.6	7.7	197	1.1	28	11	5.2	Rear	

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm)
 Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual • Boot for Head

Model Number	Drive Size		Torque		Free Speed		Weight		Length		Side to Center		Air Consumption		Exhaust
	in	mm	ft lb	Nm	rpm	lb	kg	in	mm	in	mm	cfm	l/s		
0.7 hp (0.52 kW)															
SRW07-38	3/8"	9.5	65	88	260	3.0	1.3	11.8	300	1.0	25	30	14	Front	
SRW07-50	1/2"	12.7	65	88	260	3.0	1.3	11.8	300	1.0	25	30	14	Front	

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm)
 Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual • Boot for Head



©2017 SIOUX-SMP-ON-POWER TOOLS, INC.

Offer Valid — April 6th – July 3rd, 2026



IMPACT DRIVERS



IW38TBP-2Q



IW38TBP-3P

CE

- Pistol Grip
- Belt Clip

Model Number	Drive Size	Working Torque Range ¹		Maximum Torque		Blows Per Minute	Free Speed	Weight		Length		Side To Center		Air Consumption		Socket Retainer Style
	in	ft lb	Nm	ft lb	Nm		rpm	lb	kg	in	mm	in	mm	scfm	l/s	
IW38TBP-2Q	1/4 QC	10-50	13-68	60	80	2000	8000	2.1	1.0	6.3	160	0.9	22	20	9	QC
IW38TBP-3P	3/8	10-70	13-95	70	95	2000	8000	2.1	1.0	6.3	160	0.9	22	20	9	Pin

¹ Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Suspension Bail



ID375AP-2Q



ID375AP-2QRR



IW375AP-3P

CE

- High power to weight ratio
- Smooth Impacting that creates minimal torque reaction
- Includes rubber boot for hammer case

1/4" Quick Change

3/8" Friction Ring Anvil

Model Number	Drive Size	Working Torque Range ¹		Maximum Torque		Blows Per Minute	Free Speed	Weight		Length		Side To Center		Air Consumption		Socket Retainer Style
	in	ft lb	Nm	ft lb	Nm		rpm	lb	kg	in	mm	in	mm	scfm	l/s	
ID375AP-2Q	1/4 QC	10-55	13-75	60	80	5000	4000	2.5	1.1	8.5	216	0.85	21	25	12	QC
ID375AP-2QRR	1/4 QC	10-55	13-75	60	80	5000	4000	2.5	1.1	8.5	216	0.85	21	25	12	QC
IW375AP-3P	3/8	10-95	13-130	100	135	5000	4000	2.5	1.1	8.5	216	0.85	21	25	12	Pin
IW375AP-3F	3/8	10-95	13-130	100	135	5000	4000	2.5	1.1	8.5	216	0.85	21	25	12	Ring

¹ Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual

©2017 SIOUX-SM-PON-POWER TOOLS, INC.

Offer Valid — April 6th – July 3rd, 2026