



MAKING AN IMPACT!

Receive 20% OFF Standard Discount with Purchase of an Industrial Impact!

1" Impact Wrenches



CE

- D-Handle
- Inside Trigger
- Steel Anvil Housing
- Hole/Ring Stocket Retainer

Model Number	Drive Size		Bolt Cap Grade 5		Max. Working Torque ¹		Maximum Torque		Blows Per Minute	Free Speed	Weight		Length		Side To Center		Air Consumption	
	in	mm	in	mm	ft lb	Nm	ft lb	Nm			rpm	lb	kg	in	mm	in	mm	cfm
Heavy Duty Class																		
IW1000MP-8H	1	1-1/4	32	32	1200	1630	1700	2300	825	6500	18.2	8.3	14.8	376	1.85	47	34	16
IW1000MP-8H5	1	1-1/4	32	32	1200	1630	1700	2300	825	6500	19.7	8.9	19.3	490	1.85	47	34	16
IW1000MP-8H8	1	1-1/4	32	32	1200	1630	1700	2300	825	6500	20.7	9.4	22.3	556	1.85	47	34	16
Super Duty Class																		
IW1000MH-8H	1	1-1/2	39	39	2100	2840	2500	3380	800	4000	33.4	15.2	17.0	430	2.5	65	50	24
IW1000MH-8H6	1	1-1/2	39	39	2100	2840	2500	3380	800	4000	37.3	16.9	24.1	610	2.5	65	50	24
IW1000MH-12H	1-1/2	1-1/2	39	39	2100	2840	2500	3380	800	4000	33.9	15.4	17.2	440	2.5	65	50	24
IW1000MH-5S	#5 Spline	1-1/2	39	39	2100	2840	2500	3380	800	4000	33.7	15.3	17.6	445	2.5	65	50	24

¹ Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

General: Air Inlet Size: 1/2" NPT • Recommended Hose Size: 1/2" (30 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Offer Valid — April 6th – July 3rd, 2026